## **CRAY VALLEY**

#### **Technical Data Sheet**

# Ricobond® 1756 HS

### **Powdered Maleinized Polybutadiene Dispersion**

#### **DESCRIPTION**

Ricobond® 1756 HS is a low molecular weight, high vinyl butadiene functionalized with maleic anhydride, then dispersed on amorphous silica for ease in handling. It provides enhanced adhesion of rubber compounds to metal and textiles. The anhydride functionality can react with epoxy, amine, and hydroxyl groups, while the vinyl functionality is peroxide curable, enabling the creation of unique adhesives, sealants, encapsulants, and coatings.

# PRODUCT HIGHLIGHTS / PERFORMANCE PROPERTIES

Free flowing powder

Excellent reactivity Adhesion promoter Compatibility with polar and non-polar materials

Moisture resistance Low temperature tackifier Reactive toughener for epoxies

Reactive compatibilizer for thermoplastics

#### **SUGGESTED APPLICATIONS**

Elastomers Coatings Electronics Encapsulants

Sealants Adhesives

Compatibilizers

#### TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Property	Value	Unit
Molecular Weight (Mn)*	3000	g/mol
1,2 Vinyl Content*	70	wt. %
Viscosity @ 55°C*	110,000	cps
Tg*	-25	°C
MA (Groups/Chain)*	3	-
Actives	70	%
Specific Gravity @ 25°C	1.3	-
*Resin properties		

Version Jun-24

