CRAY VALLEY

Technical Data Sheet

Ricobond® 1731 HS

Powdered Maleinized Polybutadiene Dispersion

DESCRIPTION

Ricobond® 1731 HS is a low molecular weight, low vinyl butadiene functionalized with maleic anhydride, then dispersed on amorphous silica for ease in handling. It provides enhanced adhesion of rubber compounds to metal and textiles. The anhydride functionality can react with epoxy, amine, and hydroxyl groups, enabling the creation of unique adhesives, sealants, encapsulants, and coatings.

PRODUCT HIGHLIGHTS / PERFORMANCE PROPERTIES

Free flowing powder Excellent reactivity

Adhesion promoter

Compatibility with polar and non-polar materials

Moisture resistance

Low temperature tackifier

Reactive toughener for epoxies

Reactive compatibilizer for thermoplastics

SUGGESTED APPLICATIONS

Elastomers

Coatings

Electronics

Encapsulants

Sealants Adhesives

Compatibilizers

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Property	Value	Unit
Molecular Weight (Mn)*	6,400	g/mol
1,2 Vinyl Content*	28	wt. %
Viscosity @ 45°C*	60,000	cps
Tg*	-72	°C
MA (Groups/Chain)*	9	-
Actives	70	%
Specific Gravity @ 25°C	1.3	-
*Resin properties		

Version Jun-24

